



4X2 DOUBLE SOLENOID VALVE

UFLOW AUTOMATION

Ankur Industrial Complex, Survey No: 275/276, Plot No: 31,
Nr. Intol Cast Pvt. Ltd. Shapar (Veraval) 360 024.
Dist: Rajkot Gujarat (INDIA).

Phone No: +91 2827 254343 | Cell: +91 89059 07070
Email: sales@uflowvalve.com | Website: www.uflowvalve.com

4X2 Double Solenoid Valve



Model Information

Model No	TBASODC
Type	4/2
Design	Poppet Type
Port Size	In/Out/Exhaust - Customised
Media	Compressed Air, Oxygen, Gas
Working Pressure Range	1- 3.5 bar
Orifice	6.5mm
Ambient/Medium Temperature	-5°C - 180°C
Materials of Construction	Aluminium, Silicone, Viton, Brass, Polymer

Coil Information

Operating Voltage	24V DC
Power Consumption	6W
Coil Features	High Reliability Unaffected by Voltage Surges. Easy coil changes coil lockable in 4X90 position or freely movable in between as require.
Coil Housing	IP-65

Features

- Fast response time 1000 cycle/min
- Manual override
- Lubrication Not Used
- Specially used in oxygen concentrator for medical purpose

Symbol	Model	Function	Symbol
	TBASODC	DOUBLE SOLENOID	

1	Input	2	Output
3	Exhaust	4	Output
6	Exhaust		

Port Connection

Dimensions Drawing (All Dimensions are in mm)

